

## Scheda Dati

020SMBND

Selettore a manopola, bianco, 2 posizioni, Cam B, ritorno a molla da dx



## Caratteristiche


|                         |   |
|-------------------------|---|
| <b>Gamma</b>            | Selettori a manopola non luminosi Ø 22            |
| <b>Componente</b>       | 2 posizioni                                       |
| <b>Codice</b>           | 020SMBND  |
| <b>Descrizione</b>      | Selettore a manopola, bianco, 2 posizioni, Cam B, |
| <b>Colore</b>           | Bianco  |
| <b>Peso</b>             | 27,4  |
| <b>Tariffa doganale</b> | 85365080  |
| <b>GTIN</b>             | 8052878015992                                     |

## Dati tecnici

|  |  |
|--|--|
| <b>Approvals</b>                         | CE, UL, CSA                                      |
| <b>Compliance with standards</b>         | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| <b>Compliance with standards</b>         | UNI CEI EN 45545-2, CEI EN 61373                 |
| <b>Operating temperatures</b>            | -40° ÷ +70°C                                     |
| <b>Environmental operating values</b>    | +25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30)     |
| <b>Protection degree</b>                 | IP66 - IP69 (IEC-EN60529)                        |
| <b>Protection against impact</b>         | IK06 (IEC-EN62262)                               |
| <b>Mechanical durability</b>             | 1.000.000 Operations                             |
| <b>Shock resistance</b>                  | 30g duration=18ms (EN-IEC 60068-2-27)            |
| <b>Shock resistance</b>                  | 50g duration=11ms (EN-IEC 60068-2-27)            |
| <b>Vibration resistance</b>              | 5g f= 2...500Hz (EN-IEC 60068-2-6)               |
| <b>Contact blocks configuration</b>      | Max no. 8 blocks (4+4)                           |
| <b>Material</b>                          | PA Polyamide                                     |
| <b>Locking ring material</b>             | Zamak zinc alloy                                 |
| <b>Fixing diameter</b>                   | 22.5mm - Thickness 1÷6mm                         |
| <b>Tightening torque</b>                 | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)                      |
| <b>Protection against electric shock</b> | Class II (IEC-EN61140)                           |
| <b>Warranty period</b>                   | 18 months  |


## Disegni tecnici

### CAM B







E01

E10



020E01  
020E10  
020G



0 60°

