

Datenblatt

020SMCBL5

Drehknopf-Wahlschalter, blau, 2 Positionen, Cam C, Federrücklauf von links



Merkmale




| | |
|------------------------|----------------------------------------------------------------------------|
| Baureihe | Unbeleuchtete Drehknopf-Wahlschalter Ø 22 |
| Komponenten | Drehknopf-Wahlschalter, 2 Positionen |
| Artikel-Nr. | 020SMCBL5 |
| Beschreibung | Drehknopf-Wahlschalter, blau, 2 Positionen, Cam C, Federrücklauf von links |
| Farbe | Blu |
| Gewicht - gr | 27,4 |
| Zolltarifnummer | 85365080 |
| GTIN | 8052878016050 |

Technische Daten

| | |
|------------------------------------------|--------------------------------------------------|
| Approvals | CE, UL, CSA |
| Compliance with standards | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| Compliance with standards | UNI CEI EN 45545-2, CEI EN 61373 |
| Operating temperatures | -40° ÷ +70°C |
| Environmental operating values | +25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30) |
| Protection degree | IP66 - IP69 (IEC-EN60529) |
| Protection against impact | IK06 (IEC-EN62262) |
| Mechanical durability | 1.000.000 Operations |
| Shock resistance | 30g duration=18ms (EN-IEC 60068-2-27) |
| Shock resistance | 50g duration=11ms (EN-IEC 60068-2-27) |
| Vibration resistance | 5g f= 2...500Hz (EN-IEC 60068-2-6) |
| Contact blocks configuration | Max no. 8 blocks (4+4) |
| Material | PA Polyamide |
| Locking ring material | Zamak zinc alloy |
| Fixing diameter | 22.5mm - Thickness 1÷6mm |
| Tightening torque | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in) |
| Protection against electric shock | Class II (IEC-EN61140) |
| Warranty period | 18 months |

Technische Zeichnungen

CAM C



020E01
020E10
020G

