# Datenblatt

020SMLAV
Beleuchteter Drehknopf-Wahlschalter, grün, 2 Positionen, Cam A,





## Merkmale

| | |
|---|---|
| **Baureihe** | Beleuchtete Drehknopf-Wahlschalter Ø 22 |
| **Komponenten** | Beleuchtete Drehknopf-Wahlschalter, 2 Positionen |
| **Artikel-Nr.** | 020SMLAV |
| **Beschreibung** | Beleuchteter Drehknopf-Wahlschalter, grün, 2 Positionen, Cam A, |
| **Farbe** | Verde |
| **Gewicht - gr** | 27,0 |
| **Zolltarifnummer** | 85365080 |
| **GTIN** | 8052878016210 |

## Technische Daten

| | |
|---|---|
| **Approvals** | CE, UL, CSA |
| **Compliance with standards** | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| **Compliance with standards** | UNI CEI EN 45545-2, CEI EN 61373 |
| **Operating temperatures** | -40° ÷ +70°C |
| **Environmental operating values** | +25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30) |
| **Protection degree** | IP66 - IP69 (IEC-EN60529) |
| **Protection against impact** | IK03 (IEC-EN62262) |
| **Mechanical durability** | 1.000.000 Operations |
| **Shock resistance** | 30g duration=18ms (EN-IEC 60068-2-27) |
| **Shock resistance** | 50g duration=11ms (EN-IEC 60068-2-27) |
| **Vibration resistance** | 5g f= 2...500Hz (EN-IEC 60068-2-6) |
| **Contact blocks configuration** | Max no. 2 blocks (1+1) |
| **Material** | PA Polyamide |
| **Locking ring material** | Zamak zinc alloy |
| **Fixing diameter** | 22.5mm - Thickness 1÷6mm |
| **Tightening torque** | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in) |
| **Illuminated selector switch (all versions)** | It is mandatory to use LED bulbs type 010BA9SLxxx |
| **Protection against electric shock** | Class II (IEC-EN61140) |
| **Warranty period** | 18 months |

## Technische Zeichnungen







**CAM A**




020E10
020G

**CAM A**




020E01
020E10
020G

