

Fiche technique

020SMLOA

Bouton tournant lumineux à molette, orange, 3 positions, Cam O





Caractéristiques

| | |
|-------------------------------------|--|
| Portée | Boutons tournants à molette lumineux Ø 22 |
| Composant | 3 positions |
| Code | 020SMLOA |
| Désignation des marchandises | Bouton tournant lumineux à molette, orange, 3 positions, Cam O |
| Couleur | Arancio |
| Poids | 27,0 |
| Tarif douanier | 85365080 |
| GTIN | 8052878066789 |




Données techniques

| | |
|---|---|
| Approvals | CE, UL, CSA |
| Compliance with standards | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| Compliance with standards | UNI CEI EN 45545-2, CEI EN 61373 |
| Operating temperatures | -40° ÷ +70°C |
| Environmental operating values | +25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30) |
| Protection degree | IP66 - IP69 (IEC-EN60529) |
| Protection against impact | IK03 (IEC-EN62262) |
| Mechanical durability | 1.000.000 Operations |
| Shock resistance | 30g duration=18ms (EN-IEC 60068-2-27) |
| Shock resistance | 50g duration=11ms (EN-IEC 60068-2-27) |
| Vibration resistance | 5g f= 2...500Hz (EN-IEC 60068-2-6) |
| Contact blocks configuration | Max no. 2 blocks (1+1) |
| Material | PA Polyamide |
| Locking ring material | Zamak zinc alloy |
| Fixing diameter | 22.5mm - Thickness 1÷6mm |
| Tightening torque | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in) |
| Illuminated selector switch (all versions) | It is mandatory to use LED bulbs type 010BA9SLxxx |
| Protection against electric shock | Class II (IEC-EN61140) |
| Warranty period | 18 months |

Dessins techniques






CAM 0



020E10
020E10
020G

CAM 0



020E01
020E10
020G

