

Datenblatt

020SMLOBD

Beleuchteter Drehknopf-Wahlschalter, weiß, 3 Positionen, Cam O, Federrücklauf von rechts beleuchtet



Merkmale

| | |
|------------------------|---|
| Baureihe | Beleuchtete Drehknopf-Wahlschalter Ø 22 |
| Komponenten | Beleuchtete Drehknopf-Wahlschalter, 3 Positionen |
| Artikel-Nr. | 020SMLOBD |
| Beschreibung | Beleuchteter Drehknopf-Wahlschalter, weiß, 3 Positionen, Cam O, Federrücklauf von rechts beleuchtet |
| Farbe | Bianco |
| Gewicht - gr | 27,0 |
| Zolltarifnummer | 85365080 |
| GTIN | 8052878016258 |


Technische Daten

| | |
|---|---|
| Approvals | CE, UL, CSA |
| Compliance with standards | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| Compliance with standards | UNI CEI EN 45545-2, CEI EN 61373 |
| Operating temperatures | -40° ÷ +70°C |
| Environmental operating values | +25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30) |
| Protection degree | IP66 - IP69 (IEC-EN60529) |
| Protection against impact | IK03 (IEC-EN62262) |
| Mechanical durability | 1.000.000 Operations |
| Shock resistance | 30g duration=18ms (EN-IEC 60068-2-27) |
| Shock resistance | 50g duration=11ms (EN-IEC 60068-2-27) |
| Vibration resistance | 5g f= 2...500Hz (EN-IEC 60068-2-6) |
| Contact blocks configuration | Max no. 2 blocks (1+1) |
| Material | PA Polyamide |
| Locking ring material | Zamak zinc alloy |
| Fixing diameter | 22.5mm - Thickness 1÷6mm |
| Tightening torque | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in) |
| Illuminated selector switch (all versions) | It is mandatory to use LED bulbs type 010BA9SLxxx |
| Protection against electric shock | Class II (IEC-EN61140) |
| Warranty period | 18 months |

Technische Zeichnungen



CAM O



CAM O

