

## Scheda Dati

020STACBW

Selector de llave, 2 posiciones, llave K95, Cam B, extracción llave. 0-II, metal



## Caratteristiche



|                         |  |
|-------------------------|--|
| <b>Rango</b>            | Selectores de llave Ø 22 - abrazadera de metal                                   |
| <b>Componente</b>       | Selector de llave con 2 posiciones   |
| <b>Código</b>           | 020STACBW  |
| <b>Descripción</b>      | Selector de llave, 2 posiciones, llave K95, Cam B, extracción llave. 0-II, metal |
| <b>Peso</b>             | 95,0   |
| <b>Tariffa doganale</b> | 85365080   |
| <b>GTIN</b>             | 8052878018597  |

## Dati tecnici

|  |  |
|--|--|
| <b>Approvals</b>                         | CE   |
| <b>Compliance with standards</b>         | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| <b>Compliance with standards</b>         | UNI CEI EN 45545-2                               |
| <b>Operating temperatures</b>            | -25° ÷ +65°C                                     |
| <b>Environmental operating values</b>    | +25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30)     |
| <b>Protection degree</b>                 | IP65 (IEC-EN60529)                               |
| <b>Protection against impact</b>         | IK03 (IEC-EN62262)                               |
| <b>Mechanical durability</b>             | 1.000.000 Operations                             |
| <b>Shock resistance</b>                  | 30g duration=18ms (EN-IEC 60068-2-27)            |
| <b>Shock resistance</b>                  | 50g duration=11ms (EN-IEC 60068-2-27)            |
| <b>Vibration resistance</b>              | 5g f= 2...500Hz (EN-IEC 60068-2-6)               |
| <b>Contact blocks configuration</b>      | Max no. 4 blocks (2+2)                           |
| <b>Knob or lever material</b>            | PC Polycarbonate                                 |
| <b>External bezel material</b>           | Chromed zinc alloy                               |
| <b>Locking ring material</b>             | Zamak zinc alloy                                 |
| <b>Fixing diameter</b>                   | 22.5mm - Thickness 1÷6mm                         |
| <b>Tightening torque</b>                 | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)                      |
| <b>Protection against electric shock</b> | Class II (IEC-EN61140)                           |
| <b>Warranty period</b>                   | 18 months  |

# Disegni tecnici

## CAM B



020E01  
020E10  
020G

