

Datablad

020STAMENWD

Keuzeknop, zwart, 3 posities, Cam E, veerretour van R, metaal



Kenmerken

| | |
|---------------------|---|
| Bereik | Niet-verlichte keuzeschakelaars Ø 22 ■ metalen ringmoer |
| Component | 3-positie keuzeknoppen |
| Rubriek | 020STAMENWD |
| Omschrijving | Keuzeknop, zwart, 3 posities, Cam E, veerretour van R, metaal |
| Kleur | Nero |
| Gewicht | 38,0 |
| Douanetarief | 85365080 |
| GTIN | 8052878023669 |




Technische gegevens

| | |
|--|--|
| Approvals | CE |
| Compliance with standards | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| Compliance with standards | UNI CEI EN 45545-2 |
| Operating temperatures | -25° ÷ +65°C |
| Environmental operating values | +25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30) |
| Protection degree | IP65 (IEC-EN60529) |
| Protection against impact | IK03 (IEC-EN62262) |
| Mechanical durability | 1.000.000 Operations |
| Shock resistance | 30g duration=18ms (EN-IEC 60068-2-27) |
| Shock resistance | 50g duration=11ms (EN-IEC 60068-2-27) |
| Vibration resistance | 5g f= 2...500Hz (EN-IEC 60068-2-6) |
| Contact blocks configuration | Max no. 4 blocks (2+2) |
| Knob or lever material | PC Polycarbonate |
| External bezel material | Chromed zinc alloy |
| Locking ring material | Zamak zinc alloy |
| Fixing diameter | 22.5mm - Thickness 1÷6mm |
| Tightening torque | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in) |
| Protection against electric shock | Class II (IEC-EN61140) |
| Warranty period | 18 months |

Technische tekeningen



CAM E



O20E01
O20E10
O20G

