

## Scheda Dati

020STAMLAGW

Valoväätökytkin, keltainen, 2-asentoinen, Cam A, metalli




## Caratteristiche

|                  |  |
|------------------|--|
| Range            | Valaistut valitsimet Ø 22 - metallirengas                |
| Componente       | 2-asentoinen vääntökytkin                                |
| Code             | 020STAMLAGW  |
| Kuvaus           | Valoväätökytkin, keltainen, 2-asentoinen, Cam A, metalli |
| Väriä            | Giallo   |
| Peso             | 38,0   |
| Tariffa doganale | 85365080   |
| GT               | 8052878023881  |

## Dati tecnici

|  |   |
|--|---|
| Approvals                                  | CE  |
| Compliance with standards                  | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2  |
| Compliance with standards                  | UNI CEI EN 45545-2                                |
| Operating temperatures                     | -25° ÷ +65°C                                      |
| Environmental operating values             | +25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30)      |
| Protection degree                          | IP65 (IEC-EN60529)                                |
| Protection against impact                  | IK03 (IEC-EN62262)                                |
| Mechanical durability                      | 1.000.000 Operations                              |
| Shock resistance                           | 30g duration=18ms (EN-IEC 60068-2-27)             |
| Shock resistance                           | 50g duration=11ms (EN-IEC 60068-2-27)             |
| Vibration resistance                       | 5g f= 2...500Hz (EN-IEC 60068-2-6)                |
| Contact blocks configuration               | Max no. 2 blocks (1+1)                            |
| Knob or lever material                     | PC Polycarbonate                                  |
| External bezel material                    | Chromed zinc alloy                                |
| Locking ring material                      | Zamak zinc alloy                                  |
| Fixing diameter                            | 22.5mm - Thickness 1÷6mm                          |
| Tightening torque                          | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)                       |
| Illuminated selector switch (all versions) | It is mandatory to use LED bulbs type 010BA9SLxxx |
| Protection against electric shock          | Class II (IEC-EN61140)                            |
| Warranty period                            | 18 months   |

## Disegni tecnici




### CAM A



020E10  
020G

### CAM A



020E01  
020E10  
020G

