

Hoja de datos

020STAMLOBWC

Selector luminoso de mando, blanco, 3 posiciones, Cam O, muelle con retorno al centro, metal



Características

| | |
|-------------------------|--|
| Rango | Selectores luminosos Ø 22 - abrazadera de metal |
| Componente | Selector de mando con 3 posiciones |
| Código | 020STAMLOBWC |
| Descripción | Selector luminoso de mando, blanco, 3 posiciones, Cam O, muelle con retorno al centro, metal |
| Color | Bianco |
| Peso | 38,0 |
| Arancel aduanero | 85365080 |
| GTIN | 8052878024659 |

Datos técnicos

| | |
|---|---|
| Approvals | CE |
| Compliance with standards | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| Compliance with standards | UNI CEI EN 45545-2 |
| Operating temperatures | -25° ÷ +65°C |
| Environmental operating values | +25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30) |
| Protection degree | IP65 (IEC-EN60529) |
| Protection against impact | IK03 (IEC-EN62262) |
| Mechanical durability | 1.000.000 Operations |
| Shock resistance | 30g duration=18ms (EN-IEC 60068-2-27) |
| Shock resistance | 50g duration=11ms (EN-IEC 60068-2-27) |
| Vibration resistance | 5g f= 2...500Hz (EN-IEC 60068-2-6) |
| Contact blocks configuration | Max no. 2 blocks (1+1) |
| Knob or lever material | PC Polycarbonate |
| External bezel material | Chromed zinc alloy |
| Locking ring material | Zamak zinc alloy |
| Fixing diameter | 22.5mm - Thickness 1÷6mm |
| Tightening torque | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in) |
| Illuminated selector switch (all versions) | It is mandatory to use LED bulbs type 010BA9SLxxx |
| Protection against electric shock | Class II (IEC-EN61140) |


Warranty period

18 months

Dibujos técnicos







CAM O



020E01
020E10
020G

CAM O



020E10
020E10
020G

