

## Scheda Dati

020ULAI

Modulaarinen merkkivalo H 30, väritön



## Caratteristiche

|                  |                                       |
|------------------|---------------------------------------|
| Range            | Merkkivalot Ø 22                      |
| Componente       | Modulaariset merkkivalot H30          |
| Code             | 020ULAI                               |
| Kuvaus           | Modulaarinen merkkivalo H 30, väritön |
| Väriä            | Incolore                              |
| Peso             | 13,0                                  |
| Tariffa doganale | 85365080                              |
| GT               | 8052878027308                         |

## Dati tecnici

|                                   |                                                  |
|-----------------------------------|--------------------------------------------------|
| Approvals                         | CE, UL, CSA                                      |
| Compliance with standards         | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| Compliance with standards         | UNI CEI EN 45545-2, CEI EN 61373                 |
| Operating temperatures            | -40° ÷ +70°C                                     |
| Environmental operating values    | +25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30)     |
| Protection degree                 | IP66 - IP69 (IEC-EN60529)                        |
| Protection against impact         | IK03 (IEC-EN62262)                               |
| Shock resistance                  | 30g duration=18ms (EN-IEC 60068-2-27)            |
| Shock resistance                  | 50g duration=11ms (EN-IEC 60068-2-27)            |
| Vibration resistance              | 5g f= 2...500Hz (EN-IEC 60068-2-6)               |
| Material                          | PA Polyamide                                     |
| Lens material                     | PC Polycarbonate                                 |
| Locking ring material             | PA Polyamide                                     |
| Fixing diameter                   | 22.5mm - Thickness 1÷6mm                         |
| Tightening torque                 | 1 ÷ 2,5Nm (8.8÷22.1 Lb-in)                       |
| Modular pilot light               | Must be completed with bulb holder-power supply  |
| Protection against electric shock | Class II (IEC-EN61140)                           |
| Warranty period                   | 18 months                                        |

Disegni tecnici

