

## Datasheet

020ULPA

Tamper-proof pilot light, convex lens, orange



## Features

|                |   |
|----------------|---|
| Range          | Pilot lights Ø 22                             |
| components     | Tamper-proof                                  |
| Code           | 020ULPA                                       |
| Description    | Tamper-proof pilot light, convex lens, orange |
| Colour         | Arancio                                       |
| Weight - gr    | 16.6  |
| Customs Tariff | 85365080                                      |
| GTIN           | 8052878027384                                 |

## Datasheet

|                                   |  |
|-----------------------------------|--|
| Approvals                         | CE, UL, CSA                                      |
| Compliance with standards         | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| Compliance with standards         | UNI CEI EN 45545-2, CEI EN 61373                 |
| Operating temperatures            | -40° ÷ +70°C                                     |
| Environmental operating values    | +25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30)     |
| Protection degree                 | IP66 - IP69 (IEC-EN60529)                        |
| Protection against impact         | IK03 (IEC-EN62262)                               |
| Shock resistance                  | 30g duration=18ms (EN-IEC 60068-2-27)            |
| Shock resistance                  | 50g duration=11ms (EN-IEC 60068-2-27)            |
| Vibration resistance              | 5g f= 2...500Hz (EN-IEC 60068-2-6)               |
| Material                          | PA Polyamide                                     |
| Lens material                     | PC Polycarbonate                                 |
| Locking ring material             | PA Polyamide                                     |
| Fixing diameter                   | 22.5mm - Thickness 1÷6mm                         |
| Front panel                       | Tamper proof lens                                |
| Tightening torque                 | 1 ÷ 2,5Nm (8.8÷22.1 Lb-in)                       |
| Protection against electric shock | Class II (IEC-EN61140)                           |
| Warranty period                   | 18 months  |

# Technical drawings

