

Scheda Dati

020ULPA

Voyant lumineux inviolable, cabochon bombé, orange



Caratteristiche

Portée	Voyants lumineux Ø 22
Componente	Inviolables
Code	020ULPA
Désignation des marchandises	Voyant lumineux inviolable, cabochon bombé, orange
Couleur	Arancio
Peso	16,6
Tariffa doganale	85365080
GTIN	8052878027384

Dati tecnici

Approvals	CE, UL, CSA
Compliance with standards	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
Compliance with standards	UNI CEI EN 45545-2, CEI EN 61373
Operating temperatures	-40° ÷ +70°C
Environmental operating values	+25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30)
Protection degree	IP66 - IP69 (IEC-EN60529)
Protection against impact	IK03 (IEC-EN62262)
Shock resistance	30g duration=18ms (EN-IEC 60068-2-27)
Shock resistance	50g duration=11ms (EN-IEC 60068-2-27)
Vibration resistance	5g f= 2...500Hz (EN-IEC 60068-2-6)
Material	PA Polyamide
Lens material	PC Polycarbonate
Locking ring material	PA Polyamide
Fixing diameter	22.5mm - Thickness 1÷6mm
Front panel	Tamper proof lens
Tightening torque	1 ÷ 2,5Nm (8.8÷22.1 Lb-in)
Protection against electric shock	Class II (IEC-EN61140)
Warranty period	18 months

Disegni tecnici

