

Fiche technique

020ULPG

Voyant lumineux inviolable, cabochon bombé, jaune



Caractéristiques

| | |
|-------------------------------------|---|
| Portée | Voyants lumineux Ø 22 |
| Composant | Inviolables |
| Code | 020ULPG |
| Désignation des marchandises | Voyant lumineux inviolable, cabochon bombé, jaune |
| Couleur | Giallo |
| Poids | 16,6 |
| Tarif douanier | 85365080 |
| GTIN | 8052878027414 |

Données techniques

| | |
|--|--|
| Approvals | CE, UL, CSA |
| Compliance with standards | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| Compliance with standards | UNI CEI EN 45545-2, CEI EN 61373 |
| Operating temperatures | -40° ÷ +70°C |
| Environmental operating values | +25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30) |
| Protection degree | IP66 - IP69 (IEC-EN60529) |
| Protection against impact | IK03 (IEC-EN62262) |
| Shock resistance | 30g duration=18ms (EN-IEC 60068-2-27) |
| Shock resistance | 50g duration=11ms (EN-IEC 60068-2-27) |
| Vibration resistance | 5g f= 2...500Hz (EN-IEC 60068-2-6) |
| Material | PA Polyamide |
| Lens material | PC Polycarbonate |
| Locking ring material | PA Polyamide |
| Fixing diameter | 22.5mm - Thickness 1÷6mm |
| Front panel | Tamper proof lens |
| Tightening torque | 1 ÷ 2,5Nm (8.8÷22.1 Lb-in) |
| Protection against electric shock | Class II (IEC-EN61140) |
| Warranty period | 18 months |

Dessins techniques

