

## Fiche technique

020ULR

Voyant lumineux modulaire, rouge



## Caractéristiques

|                                     |                                  |
|-------------------------------------|----------------------------------|
| <b>Portée</b>                       | Voyants lumineux Ø 22            |
| <b>Composant</b>                    | Modulaires                       |
| <b>Code</b>                         | 020ULR                           |
| <b>Désignation des marchandises</b> | Voyant lumineux modulaire, rouge |
| <b>Couleur</b>                      | Rosso                            |
| <b>Poids</b>                        | 9,0                              |
| <b>Tarif douanier</b>               | 85365080                         |
| <b>GTIN</b>                         | 8052878027452                    |

## Données techniques

|                                          |                                                  |
|------------------------------------------|--------------------------------------------------|
| <b>Approvals</b>                         | CE, UL, CSA                                      |
| <b>Compliance with standards</b>         | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| <b>Compliance with standards</b>         | UNI CEI EN 45545-2, CEI EN 61373                 |
| <b>Operating temperatures</b>            | -40° ÷ +70°C                                     |
| <b>Environmental operating values</b>    | +25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30)     |
| <b>Protection degree</b>                 | IP66 - IP69 (IEC-EN60529)                        |
| <b>Protection against impact</b>         | IK03 (IEC-EN62262)                               |
| <b>Shock resistance</b>                  | 30g duration=18ms (EN-IEC 60068-2-27)            |
| <b>Shock resistance</b>                  | 50g duration=11ms (EN-IEC 60068-2-27)            |
| <b>Vibration resistance</b>              | 5g f= 2...500Hz (EN-IEC 60068-2-6)               |
| <b>Material</b>                          | PA Polyamide                                     |
| <b>Lens material</b>                     | PC Polycarbonate                                 |
| <b>Locking ring material</b>             | PA Polyamide                                     |
| <b>Fixing diameter</b>                   | 22.5mm - Thickness 1÷6mm                         |
| <b>Tightening torque</b>                 | 1 ÷ 2,5Nm (8.8÷22.1 Lb-in)                       |
| <b>Modular pilot light</b>               | Must be completed with bulb holder-power supply  |
| <b>Protection against electric shock</b> | Class II (IEC-EN61140)                           |
| <b>Warranty period</b>                   | 18 months                                        |

# Dessins techniques

