


Fiche technique

030F1P

Élément de contact N.O.+N.C., protégé



Caractéristiques

Portée	Blocs de contacts Ø 30
Composant	1 N.O.+1 N.C.
Code	030F1P
Désignation des marchandises	Élément de contact N.O.+N.C., protégé
Couleur	Grigio RAL7035
Poids	38,0
Tarif douanier	85365080
GTIN	8052878027971

Données techniques

Approvals	CE, UL, CSA
Compliance with standards	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
Operating temperatures	-25° ÷ +65°C
Protection degree	IP20 (IEC-EN60529) with protection 030PFA-PFC-PF1
Mechanical durability	5.000.000 Operations
Housing material	PC Polycarbonate
Terminal screw	Tightening torque 0.8÷1 Nm (IEC-EN60947-1)
Terminal screw head shape	Combined:cross Phillips2 or slotted flat D.5mm max
Terminal screw material	Zinc plated steel
Terminal screw connections	min 1x0.5mm ² (20AWG) - max 2x2.5mm ² (14AWG)
Cable lugs	Fork type "spring spade" for screw M3.5 / W=6.4mm
Contact material	Ag 1000/1000
Contact movement	Slow action contact
Contacts	Self cleaning by pads creeping
NC contacts (all versions)	Positive opening function (IEC-EN60947-5-1 ann.K)
Rated insulation voltage	Ui 690V - Uimp 4KV (IEC-EN60947-1)
Rated thermal current	Ith 10A (IEC-EN60947-1)
Protection against electric shock	Class II (IEC-EN61140)
Short-circuit protective device	10A cartridge fuse gG 10x38mm (IEC-EN60947-5-1)
Electrical ratings	AC15-DC13 (IEC-EN60947-5-1) - A600-P300 (UL 508)
AC Performances	AC 24V-10A, 120V-6A, 240V-3A, 600V-1.2A

DC Performances

DC 24V-5A, 120V-1.1A, 240V-0.55A

Warranty period

18 months

Dessins techniques

