

## Scheda Dati

030LE14B

Voyant lumineux, blanc, sans lampe, E14 7W alimentation directe



## Caratteristiche

|                                     |   |
|-------------------------------------|---|
| <b>Portée</b>                       | Voyants lumineux Ø 30   |
| <b>Componente</b>                   | Ampoules E14, alimentation directe                              |
| <b>Code</b>                         | 030LE14B  |
| <b>Désignation des marchandises</b> | Voyant lumineux, blanc, sans lampe, E14 7W alimentation directe |
| <b>Couleur</b>                      | Bianco  |
| <b>Peso</b>                         | 42,0  |
| <b>Tariffa doganale</b>             | 85365080  |
| <b>GTIN</b>                         | 8052878028817   |

## Dati tecnici

|                                   |   |
|-----------------------------------|---|
| <b>Approvals</b>                  | CE  |
| <b>Compliance with standards</b>  | IEC-ENC60947-1, IEC-EN60947-5-1                                     |
| <b>Operating temperatures</b>     | -25° ÷ +65°C  |
| <b>Protection degree</b>          | IP65 (IEC-EN60529)  |
| <b>Material</b>                   | PA Polyamide  |
| <b>External bezel material</b>    | Chromed zinc alloy  |
| <b>Lens material</b>              | PC Polycarbonate  |
| <b>Fixing diameter</b>            | 30.5mm - Thickness 1÷6mm  |
| <b>Tightening torque</b>          | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)   |
| <b>Terminal screw</b>             | Tightening torque 0.8÷1 Nm (IEC-EN60947-1)                          |
| <b>Terminal screw head shape</b>  | Combined:cross Phillips2 or slotted flat D.5mm max                  |
| <b>Terminal screw material</b>    | Zinc plated steel   |
| <b>Terminal screw connections</b> | min 1x0.5mm <sup>2</sup> (20AWG) - max 2x2.5mm <sup>2</sup> (14AWG) |
| <b>Bulb type</b>                  | E14 250V AC-DC 10W max (not included)                               |
| <b>Warranty period</b>            | 18 months   |

## Disegni tecnici

