

Fiche technique

030LFIA

Voyant lumineux, montage affleurant, orange



Caractéristiques

Portée	Voyants lumineux Ø 30
Composant	Voyants lumineux
Code	030LFIA
Désignation des marchandises	Voyant lumineux, montage affleurant, orange
Couleur	Arancio
Poids	40,0
Tarif douanier	85365080
GTIN	8052878064921

Données techniques

Approvals	CE, UL, CSA
Compliance with standards	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
Compliance with standards	UNI CEI EN 45545-2, CEI EN 61373
Operating temperatures	-25° ÷ +65°C
Environmental operating values	+25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30)
Protection degree	IP65 (IEC-EN60529)
Protection against impact	IK04 (IEC-EN62262)
Shock resistance	30g duration=18ms (EN-IEC 60068-2-27)
Shock resistance	50g duration=11ms (EN-IEC 60068-2-27)
Vibration resistance	5g f= 2...500Hz (EN-IEC 60068-2-6)
External bezel material	Anodized aluminum
Lens material	PC Polycarbonate
Locking ring material	Zamak zinc alloy
Fixing diameter	30.5mm - Thickness 1÷6mm
Front panel	Tamper proof lens
Tightening torque	2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)
Modular pilot light	Must be completed with bulb holder-power supply
Protection against electric shock	Class I (IEC-EN61140)
Warranty period	18 months

Dessins techniques

