

Datenblatt

030LFIBL

Kontrolllampe, flächenbündig, blau



Merkmale

| | |
|------------------------|------------------------------------|
| Baureihe | Kontrolllampen Ø 30 |
| Komponenten | Kontrolllampen |
| Artikel-Nr. | 030LFIBL |
| Beschreibung | Kontrolllampe, flächenbündig, blau |
| Farbe | Blu |
| Gewicht - gr | 40,0 |
| Zolltarifnummer | 85365080 |
| GTIN | 8052878028886 |

Technische Daten

| | |
|--|--|
| Approvals | CE, UL, CSA |
| Compliance with standards | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| Compliance with standards | UNI CEI EN 45545-2, CEI EN 61373 |
| Operating temperatures | -25° ÷ +65°C |
| Environmental operating values | +25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30) |
| Protection degree | IP65 (IEC-EN60529) |
| Protection against impact | IK04 (IEC-EN62262) |
| Shock resistance | 30g duration=18ms (EN-IEC 60068-2-27) |
| Shock resistance | 50g duration=11ms (EN-IEC 60068-2-27) |
| Vibration resistance | 5g f= 2...500Hz (EN-IEC 60068-2-6) |
| External bezel material | Anodized aluminum |
| Lens material | PC Polycarbonate |
| Locking ring material | Zamak zinc alloy |
| Fixing diameter | 30.5mm - Thickness 1÷6mm |
| Front panel | Tamper proof lens |
| Tightening torque | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in) |
| Modular pilot light | Must be completed with bulb holder-power supply |
| Protection against electric shock | Class I (IEC-EN61140) |
| Warranty period | 18 months |

Technische Zeichnungen

