

Datenblatt

030LFIR

Kontrolllampe, flächenbündig, rot



Merkmale

Baureihe	Kontrolllampen Ø 30
Komponenten	Kontrolllampen
Artikel-Nr.	030LFIR
Beschreibung	Kontrolllampe, flächenbündig, rot
Farbe	Rosso
Gewicht - gr	40,0
Zolltarifnummer	85365080
GTIN	8052878028930

Technische Daten

Approvals	CE, UL, CSA
Compliance with standards	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
Compliance with standards	UNI CEI EN 45545-2, CEI EN 61373
Operating temperatures	-25° ÷ +65°C
Environmental operating values	+25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30)
Protection degree	IP65 (IEC-EN60529)
Protection against impact	IK04 (IEC-EN62262)
Shock resistance	30g duration=18ms (EN-IEC 60068-2-27)
Shock resistance	50g duration=11ms (EN-IEC 60068-2-27)
Vibration resistance	5g f= 2...500Hz (EN-IEC 60068-2-6)
External bezel material	Anodized aluminum
Lens material	PC Polycarbonate
Locking ring material	Zamak zinc alloy
Fixing diameter	30.5mm - Thickness 1÷6mm
Front panel	Tamper proof lens
Tightening torque	2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)
Modular pilot light	Must be completed with bulb holder-power supply
Protection against electric shock	Class I (IEC-EN61140)
Warranty period	18 months

Technische Zeichnungen

