

Datenblatt

030LSBL

Kontrolllampe, blau, ohne LED BA9S, Direktversorgung



Merkmale

| | |
|------------------------|--|
| Baureihe | Kontrolllampen Ø 30 |
| Komponenten | Kontrolllampen BA9S, Direktversorgung |
| Artikel-Nr. | 030LSBL |
| Beschreibung | Kontrolllampe, blau, ohne LED BA9S, Direktversorgung |
| Farbe | Blu |
| Gewicht - gr | 68,0 |
| Zolltarifnummer | 85365080 |
| GTIN | 8052878029234 |

Technische Daten

| | |
|--|--|
| Approvals | CE |
| Compliance with standards | IEC-ENC60947-1, IEC-EN60947-5-1 |
| Operating temperatures | -25° ÷ +65°C |
| Protection degree | IP65 (IEC-EN60529) |
| Housing material | PA Polyamide |
| External bezel material | Chromed zinc alloy |
| Lens material | PC Polycarbonate |
| Fixing diameter | 30.5mm - Thickness 1÷6mm |
| Tightening torque | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in) |
| Terminal screw | Tightening torque 0.8÷1 Nm (IEC-EN60947-1) |
| Terminal screw head shape | Combined:cross Phillips2 or slotted flat D.5mm max |
| Terminal screw material | Zinc plated steel |
| Cable lugs | Fork type "spring spade" for screw M3.5 / W=6.4mm |
| Bulb type | Ba9S 400V - 2W max (not included) |
| Rated insulation voltage | Ui 690V - Uimp 4KV (IEC-EN60947-1) |
| Protection against electric shock | Class II (IEC-EN61140) |
| Warranty period | 18 months |

Technische Zeichnungen

