# Datasheet

030LSBL
Pilot light, blue, without led BA9S, direct supply





## Features

| | |
|---|---|
| **Range** | Pilot lights Ø 30 |
| **components** | BA9S, direct supply |
| **Code** | 030LSBL |
| **Description** | Pilot light, blue, without led BA9S, direct supply |
| **Colour** | Blu |
| **Weight - gr** | 68.0 |
| **Customs Tariff** | 85365080 |
| **GTIN** | 8052878029234 |

## Datasheet

| | |
|---|---|
| **Approvals** | CE |
| **Compliance with standards** | IEC-ENC60947-1, IEC-EN60947-5-1 |
| **Operating temperatures** | -25° ÷ +65°C |
| **Protection degree** | IP65 (IEC-EN60529) |
| **Housing material** | PA Polyamide |
| **External bezel material** | Chromed zinc alloy |
| **Lens material** | PC Polycarbonate |
| **Fixing diameter** | 30.5mm - Thickness 1÷6mm |
| **Tightening torque** | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in) |
| **Terminal screw** | Tightening torque 0.8÷1 Nm (IEC-EN60947-1) |
| **Terminal screw head shape** | Combined:cross Phillips2 or slotted flat D.5mm max |
| **Terminal screw material** | Zinc plated steel |
| **Cable lugs** | Fork type "spring spade" for screw M3.5 / W=6.4mm |
| **Bulb type** | Ba9S 400V - 2W max (not included) |
| **Rated insulation voltage** | Ui 690V - Uimp 4KV (IEC-EN60947-1) |
| **Protection against electric shock** | Class II (IEC-EN61140) |
| **Warranty period** | 18 months |

## Technical drawings







