

Hoja de datos

030LSBL

Testigo, azul, sin led BA9S, alimentación directa



Características

Rango	Testigos Ø 30
Componente	Testigos BA9S, alimentación directa
Código	030LSBL
Descripción	Testigo, azul, sin led BA9S, alimentación directa
Color	Blu
Peso	68,0
Arancel aduanero	85365080
GTIN	8052878029234

Datos técnicos

Approvals	CE
Compliance with standards	IEC-ENC60947-1, IEC-EN60947-5-1
Operating temperatures	-25° ÷ +65°C
Protection degree	IP65 (IEC-EN60529)
Housing material	PA Polyamide
External bezel material	Chromed zinc alloy
Lens material	PC Polycarbonate
Fixing diameter	30.5mm - Thickness 1÷6mm
Tightening torque	2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)
Terminal screw	Tightening torque 0.8÷1 Nm (IEC-EN60947-1)
Terminal screw head shape	Combined:cross Phillips2 or slotted flat D.5mm max
Terminal screw material	Zinc plated steel
Cable lugs	Fork type "spring spade" for screw M3.5 / W=6.4mm
Bulb type	Ba9S 400V - 2W max (not included)
Rated insulation voltage	Ui 690V - Uimp 4KV (IEC-EN60947-1)
Protection against electric shock	Class II (IEC-EN61140)
Warranty period	18 months

Dibujos técnicos

