

Datasheet

030LSG

Pilot light, yellow, without led BA9S, direct supply



Features

Range	Pilot lights Ø 30
components	BA9S, direct supply
Code	030LSG
Description	Pilot light, yellow, without led BA9S, direct supply
Colour	Giallo
Weight - gr	61.0
Customs Tariff	85365080
GTIN	8052878029258

Datasheet

Approvals	CE
Compliance with standards	IEC-ENC60947-1, IEC-EN60947-5-1
Operating temperatures	-25° ÷ +65°C
Protection degree	IP65 (IEC-EN60529)
Housing material	PA Polyamide
External bezel material	Chromed zinc alloy
Lens material	PC Polycarbonate
Fixing diameter	30.5mm - Thickness 1÷6mm
Tightening torque	2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)
Terminal screw	Tightening torque 0.8÷1 Nm (IEC-EN60947-1)
Terminal screw head shape	Combined:cross Phillips2 or slotted flat D.5mm max
Terminal screw material	Zinc plated steel
Cable lugs	Fork type "spring spade" for screw M3.5 / W=6.4mm
Bulb type	Ba9S 400V - 2W max (not included)
Rated insulation voltage	Ui 690V - Uimp 4KV (IEC-EN60947-1)
Protection against electric shock	Class II (IEC-EN61140)
Warranty period	18 months

Technical drawings

