

## Scheda Dati

030LSV

Controlelamp, groen, zonder led BA9S, directe voeding



## Caratteristiche

<b>Bereik</b>	Controlelamp Ø 30
<b>Componente</b>	Controlelamp BA9S, directe voeding
<b>Rubriek</b>	030LSV
<b>Omschrijving</b>	Controlelamp, groen, zonder led BA9S, directe voeding
<b>Kleur</b>	Verde
<b>Peso</b>	61,0
<b>Tariffa doganale</b>	85365080
<b>GTIN</b>	8052878029289

## Dati tecnici

<b>Approvals</b>	CE
<b>Compliance with standards</b>	IEC-ENC60947-1, IEC-EN60947-5-1
<b>Operating temperatures</b>	-25° ÷ +65°C
<b>Protection degree</b>	IP65 (IEC-EN60529)
<b>Housing material</b>	PA Polyamide
<b>External bezel material</b>	Chromed zinc alloy
<b>Lens material</b>	PC Polycarbonate
<b>Fixing diameter</b>	30.5mm - Thickness 1÷6mm
<b>Tightening torque</b>	2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)
<b>Terminal screw</b>	Tightening torque 0.8÷1 Nm (IEC-EN60947-1)
<b>Terminal screw head shape</b>	Combined:cross Phillips2 or slotted flat D.5mm max
<b>Terminal screw material</b>	Zinc plated steel
<b>Cable lugs</b>	Fork type "spring spade" for screw M3.5 / W=6.4mm
<b>Bulb type</b>	Ba9S 400V - 2W max (not included)
<b>Rated insulation voltage</b>	Ui 690V - Uimp 4KV (IEC-EN60947-1)
<b>Protection against electric shock</b>	Class II (IEC-EN61140)
<b>Warranty period</b>	18 months

## Disegni tecnici

