

## Datasheet

030MF4T

Joystick, flush-mount, 4-position, 4 Spring Return







## Features

<b>Range</b>	Joysticks Ø 30
<b>components</b>	4-position
<b>Code</b>	030MF4T
<b>Description</b>	Joystick, flush-mount, 4-position, 4 Spring Return
<b>Colour</b>	Nero
<b>Weight - gr</b>	54.0
<b>Customs Tariff</b>	85365080
<b>GTIN</b>	8052878029425

## Datasheet

<b>Approvals</b>	CE, UL, CSA
<b>Compliance with standards</b>	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
<b>Compliance with standards</b>	UNI CEI EN 45545-2, CEI EN 61373
<b>Operating temperatures</b>	-25° ÷ +65°C
<b>Protection degree</b>	IP65 (IEC-EN60529)
<b>Protection against impact</b>	IK04 (IEC-EN62262)
<b>Mechanical durability</b>	1.000.000 Operations
<b>Shock resistance</b>	30g duration=18ms (EN-IEC 60068-2-27)
<b>Shock resistance</b>	50g duration=11ms (EN-IEC 60068-2-27)
<b>Vibration resistance</b>	5g f= 2...500Hz (EN-IEC 60068-2-6)
<b>Contact blocks configuration</b>	Max no. 4 blocks (2+2)
<b>Material</b>	PA Polyamide
<b>Cap or bellow material</b>	Silicon rubber
<b>External bezel material</b>	Anodized aluminum
<b>Internal parts material</b>	Lever,springs,bushing - stainless steel AISI 304
<b>Internal parts material</b>	Sliding bushing made in brass
<b>Locking ring material</b>	Zamak zinc alloy
<b>Fixing diameter</b>	30.5mm - Thickness 1÷6mm
<b>Tightening torque</b>	2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)
<b>Protection against electric shock</b>	Class I (IEC-EN61140)
<b>Warranty period</b>	18 months

# Technical drawings



020E10  
020E10  
020E01  
020E01  
020G

