

## Scheda Dati

### 030MPPNB

Manipulador, 2 posições, 2 Permanentes, com bloqueio, 2 N.O.+2 N.C.



## Caratteristiche

|                  |                                                                     |
|------------------|---------------------------------------------------------------------|
| Gama             | Manipuladores Ø 30                                                  |
| Componente       | 2 posições com trava de segurança                                   |
| Código           | 030MPPNB                                                            |
| Descrição        | Manipulador, 2 posições, 2 Permanentes, com bloqueio, 2 N.O.+2 N.C. |
| Cor              | Nero                                                                |
| Peso             | 172,0                                                               |
| Tariffa doganale | 85365080                                                            |
| GTIN             | 8052878067526                                                       |

## Dati tecnici

|                                   |                                                  |
|-----------------------------------|--------------------------------------------------|
| Approvals                         | CE                                               |
| Compliance with standards         | IEC-ENC60947-1, IEC-EN60947-5-1                  |
| Operating temperatures            | -25° ÷ +65°C                                     |
| Protection degree                 | IP65 Front panel / IP2X terminals(IEC-EN60529)   |
| Mechanical durability             | 2.000.000 Operations                             |
| Cap or bellow material            | Silicon rubber                                   |
| Housing material                  | PA Polyamide                                     |
| External bezel material           | Chromed zinc alloy                               |
| Internal parts material           | Lever,springs,bushing - stainless steel AISI 304 |
| Actuation force                   | 13N                                              |
| Fixing diameter                   | 30.5mm - Thickness 1÷6mm                         |
| Tightening torque                 | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)                      |
| Actuation with safety interlock   | Red button - lift to unlock                      |
| Protection against electric shock | Class II (IEC-EN61140)                           |
| Contact block characteristics     | See technical features of 030F1 or 030FA+030FCR  |
| Contact block                     | Included                                         |
| Warranty period                   | 18 months                                        |

Disegni tecnici

