


Fiche technique

030MPPRN

Manipulateur, 2 positions, 2 Maintenues, 2 N.O. + 2 N.C.




Caractéristiques

| | |
|-------------------------------------|--|
| Portée | Manipulateurs Ø 30 |
| Composant | 2 positions, schéma spécial |
| Code | 030MPPRN |
| Désignation des marchandises | Manipulateur, 2 positions, 2 Maintenues, 2 N.O. + 2 N.C. |
| Couleur | Nero |
| Poids | 147,0 |
| Tarif douanier | 85365080 |
| GTIN | 8052878029494 |

Données techniques

| | |
|--|--|
| Approvals | CE, UL, CSA |
| Compliance with standards | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| Operating temperatures | -25° ÷ +65°C |
| Protection degree | IP65 Front panel / IP2X terminals(IEC-EN60529) |
| Mechanical durability | 2.000.000 Operations |
| Cap or bellow material | Silicon rubber |
| Housing material | PA Polyamide |
| External bezel material | Chromed zinc alloy |
| Internal parts material | Lever, springs, bushing - stainless steel AISI 304 |
| Actuation force | 13N |
| Fixing diameter | 30.5mm - Thickness 1÷6mm |
| Tightening torque | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in) |
| Protection against electric shock | Class II (IEC-EN61140) |
| Contact block characteristics | See technical features of 030F1 or 030FA+030FCR |
| Contact block | Included |
| Warranty period | 18 months |

Dessins techniques



① ② ③

