

## Scheda Dati

030MPTTTN

Ohjaussauva, 4 asentoa, 1 pysyvää, 3 väliaikaista, 2 N.O.+2 N.C.



## Caratteristiche

|                  |                                                                  |
|------------------|------------------------------------------------------------------|
| Range            | Ohjaussauvat Ø 30                                                |
| Componente       | Ohjaussauvat 4-asentoinen                                        |
| Code             | 030MPTTTN                                                        |
| Kuvaus           | Ohjaussauva, 4 asentoa, 1 pysyvää, 3 väliaikaista, 2 N.O.+2 N.C. |
| Väriä            | Nero                                                             |
| Peso             | 155,0                                                            |
| Tariffa doganale | 85365080                                                         |
| GT               | 8052878029524                                                    |

## Dati tecnici

|                                   |                                                    |
|-----------------------------------|----------------------------------------------------|
| Approvals                         | CE, UL, CSA                                        |
| Compliance with standards         | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2   |
| Operating temperatures            | -25° ÷ +65°C                                       |
| Protection degree                 | IP65 Front panel / IP2X terminals(IEC-EN60529)     |
| Mechanical durability             | 2.000.000 Operations                               |
| Cap or bellow material            | Silicon rubber                                     |
| Housing material                  | PA Polyamide                                       |
| External bezel material           | Chromed zinc alloy                                 |
| Internal parts material           | Lever, springs, bushing - stainless steel AISI 304 |
| Actuation force                   | 13N                                                |
| Fixing diameter                   | 30.5mm - Thickness 1÷6mm                           |
| Tightening torque                 | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)                        |
| Protection against electric shock | Class II (IEC-EN61140)                             |
| Contact block characteristics     | See technical features of 030F1 or 030FA+030FCR    |
| Contact block                     | Included                                           |
| Warranty period                   | 18 months                                          |

Disegni tecnici

