


## Scheda Dati

030MTN2F1

Ohjaussauva, 2 asentoa, 1 pysyvä, 1 väliaikainen, 2 N.O.+2 N.C.



## Caratteristiche

<b>Range</b>	Ohjaussauvat Ø 30
<b>Componente</b>	Ohjaussauvat 2-asentoinen vastakkaiset
<b>Code</b>	030MTN2F1
<b>Kuvaus</b>	Ohjaussauva, 2 asentoa, 1 pysyvä, 1 väliaikainen, 2 N.O.+2 N.C.
<b>Väriä</b>	Nero
<b>Peso</b>	155,0
<b>Tariffa doganale</b>	85365080
<b>GT</b>	8052878029531

## Dati tecnici

<b>Approvals</b>	CE, UL, CSA
<b>Compliance with standards</b>	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
<b>Operating temperatures</b>	-25° ÷ +65°C
<b>Protection degree</b>	IP65 Front panel / IP2X terminals(IEC-EN60529)
<b>Mechanical durability</b>	2.000.000 Operations
<b>Cap or bellow material</b>	Silicon rubber
<b>Housing material</b>	PA Polyamide
<b>External bezel material</b>	Chromed zinc alloy
<b>Internal parts material</b>	Lever, springs, bushing - stainless steel AISI 304
<b>Actuation force</b>	13N
<b>Fixing diameter</b>	30.5mm - Thickness 1÷6mm
<b>Tightening torque</b>	2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)
<b>Protection against electric shock</b>	Class II (IEC-EN61140)
<b>Contact block characteristics</b>	See technical features of 030F1 or 030FA+030FCR
<b>Contact block</b>	Included
<b>Warranty period</b>	18 months

## Disegni tecnici

