


Scheda Dati

030MTTTTN

Manipolatore, 4 posizioni, 4 Temporanee, 2 N.O.+2 N.C.



Caratteristiche

| | |
|-------------------------|--|
| Gamma | Manipolatori Ø 30 |
| Componente | 4 posizioni |
| Codice | 030MTTTTN |
| Descrizione | Manipolatore, 4 posizioni, 4 Temporanee, 2 N.O.+2 N.C. |
| Colore | Nero |
| Peso | 155,0 |
| Tariffa doganale | 85365080 |
| GTIN | 8052878029616 |

Dati tecnici

| | |
|--|--|
| Approvals | CE, UL, CSA |
| Compliance with standards | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| Operating temperatures | -25° ÷ +65°C |
| Protection degree | IP65 Front panel / IP2X terminals(IEC-EN60529) |
| Mechanical durability | 2.000.000 Operations |
| Cap or bellow material | Silicon rubber |
| Housing material | PA Polyamide |
| External bezel material | Chromed zinc alloy |
| Internal parts material | Lever, springs, bushing - stainless steel AISI 304 |
| Actuation force | 13N |
| Fixing diameter | 30.5mm - Thickness 1÷6mm |
| Tightening torque | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in) |
| Protection against electric shock | Class II (IEC-EN61140) |
| Contact block characteristics | See technical features of 030F1 or 030FA+030FCR |
| Contact block | Included |
| Warranty period | 18 months |

Disegni tecnici

