

Datenblatt

030PFAFLG

Beleuchteter Notfall-Pilztaster Ø 38, flächenbündig, momentan, gelb



Merkmale

Baureihe	Beleuchtete Pilztaster Ø 30
Komponenten	Pilztaster Ø 38
Artikel-Nr.	030PFAFLG
Beschreibung	Beleuchteter Notfall-Pilztaster Ø 38, flächenbündig, momentan, gelb
Farbe	Giallo
Gewicht - gr	50,0
Zolltarifnummer	85365080
GTIN	8052878029784

Dati tecnici

Approvals	CE, UL, CSA
Compliance with standards	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
Compliance with standards	UNI CEI EN 45545-2, CEI EN 61373
Operating temperatures	-25° ÷ +65°C
Environmental operating values	+25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30)
Protection degree	IP65 (IEC-EN60529)
Protection against impact	IK04 (IEC-EN62262)
Mechanical durability	3.000.000 Operations
Shock resistance	30g duration=18ms (EN-IEC 60068-2-27)
Shock resistance	50g duration=11ms (EN-IEC 60068-2-27)
Vibration resistance	5g f= 2...500Hz (EN-IEC 60068-2-6)
Contact blocks configuration	Max no. 6 blocks (3+3)
Button/mushroom material (illuminated type)	PC Polycarbonate
Button or knob material	PA Polyamide
External bezel material	Anodized aluminum
Locking ring material	Zamak zinc alloy
Fixing diameter	30.5mm - Thickness 1÷6mm
Tightening torque	2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)
Actuation type	Spring return
Protection against electric shock	Class I (IEC-EN61140)

Warranty period

18 months

Disegni tecnici

