

## Hoja de datos

030PFBA2FC

Pulsador fungiforme Ø 35, con desenganche, rojo, desenganche con llave K37, 2 N.C.



## Características

|                  |  |
|------------------|--|
| Rango            | Pulsadores de emergencia Ø 30  |
| Componente       | Pulsadores fungiformes Ø 35, desenganche con llave                                 |
| Código           | 030PFBA2FC   |
| Descripción      | Pulsador fungiforme Ø 35, con desenganche, rojo, desenganche con llave K37, 2 N.C. |
| Color            | Rosso  |
| Peso             | 183,0  |
| Arancel aduanero | 85365080   |
| GTIN             | 8052878030032  |

## Datos técnicos

|                                   |  |
|-----------------------------------|--|
| Approvals                         | CE, (UL-CSA 030F1-030FA-030FC-030FAA-030FCR only)  |
| Compliance with standards         | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2   |
| Operating temperatures            | -25° ÷ +65°C                                       |
| Protection degree                 | IP65 (IEC-EN60529)                                 |
| Mechanical durability             | 500.000 Operations                                 |
| External bezel material           | Chromed zinc alloy                                 |
| Button material                   | PA Polyamide                                       |
| Housing material                  | PA Polyamide + chrome                              |
| Fixing diameter                   | 30.5mm - Thickness 1÷6mm                           |
| Tightening torque                 | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)                        |
| Actuation type                    | With mechanical latching - twist to release        |
| Protection against electric shock | Class II (IEC-EN61140)                             |
| Contact block                     | Included   |
| Contact block characteristics     | See technical features of 030FAP - 030FCP - 030F1P |
| Warranty period                   | 18 months  |

