


## Scheda Dati

030PFFAR2FC

Bouton-poussoir coup de poing Ø 60, déverrouillage par rotation, rouge, 2 N.C.



## Caratteristiche

|                                     |  |
|-------------------------------------|--|
| <b>Portée</b>                       | Boutons-poussoirs d'arrêt d'urgence Ø 30                                       |
| <b>Componente</b>                   | Coup de poing Ø 60, déverrouillage rotation                                    |
| <b>Code</b>                         | 030PFFAR2FC  |
| <b>Désignation des marchandises</b> | Bouton-poussoir coup de poing Ø 60, déverrouillage par rotation, rouge, 2 N.C. |
| <b>Couleur</b>                      | Rosso  |
| <b>Peso</b>                         | 132,0  |
| <b>Tariffa doganale</b>             | 85365080   |
| <b>GTIN</b>                         | 8052878030117  |

## Dati tecnici

|  |  |
|--|--|
| <b>Approvals</b>                         | CE, (UL-CSA 030F1-030FA-030FC-030FAA-030FCR only)  |
| <b>Compliance with standards</b>         | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2   |
| <b>Operating temperatures</b>            | -25° ÷ +65°C                                       |
| <b>Protection degree</b>                 | IP65 (IEC-EN60529)                                 |
| <b>Mechanical durability</b>             | 500.000 Operations                                 |
| <b>External bezel material</b>           | Chromed zinc alloy                                 |
| <b>Button material</b>                   | PA Polyamide                                       |
| <b>Housing material</b>                  | PA Polyammide + chrome                             |
| <b>Fixing diameter</b>                   | 30.5mm - Thickness 1÷6mm                           |
| <b>Tightening torque</b>                 | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)                        |
| <b>Actuation type</b>                    | With mechanical latching - twist to release        |
| <b>Protection against electric shock</b> | Class II (IEC-EN61140)                             |
| <b>Contact block</b>                     | Included   |
| <b>Contact block characteristics</b>     | See technical features of 030FAP - 030FCP - 030F1P |
| <b>Warranty period</b>                   | 18 months  |

## Disegni tecnici

