


Scheda Dati

030PFFARFAFC

Kupukantainen painike Ø 60, avaus kiertämällä, punainen, N.O. + N.C.



Caratteristiche

Range	Hätäpainikkeet Ø 30
Componente	Kupukantaiset painikkeet Ø 60, avaus kiertämällä
Code	030PFFARFAFC
Kuvaus	Kupukantainen painike Ø 60, avaus kiertämällä, punainen, N.O. + N.C.
Väriä	Rosso
Peso	117,0
Tariffa doganale	85365080
GT	8052878069124

Dati tecnici

Approvals	CE, (UL-CSA 030F1-030FA-030FC-030FAA-030FCR only)
Compliance with standards	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
Operating temperatures	-25° ÷ +65°C
Protection degree	IP65 (IEC-EN60529)
Mechanical durability	500.000 Operations
External bezel material	Chromed zinc alloy
Button material	PA Polyamide
Housing material	PA Polyammide + chrome
Fixing diameter	30.5mm - Thickness 1÷6mm
Tightening torque	2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)
Actuation type	With mechanical latching - twist to release
Protection against electric shock	Class II (IEC-EN61140)
Contact block	Included
Contact block characteristics	See technical features of 030FAP - 030FCP - 030F1P
Warranty period	18 months

Disegni tecnici

