


## Datablad

030PFFARFAFC

Noodstopknop Ø 60, draaiontgrendeling, rood, N.O. + N.C.



## Kenmerken

|                     |  |
|---------------------|--|
| <b>Bereik</b>       | Noodknoppen Ø 30   |
| <b>Component</b>    | Noodstopknoppen Ø 60, ontgrendeling rotatie              |
| <b>Rubriek</b>      | 030PFFARFAFC   |
| <b>Omschrijving</b> | Noodstopknop Ø 60, draaiontgrendeling, rood, N.O. + N.C. |
| <b>Kleur</b>        | Rosso  |
| <b>Gewicht</b>      | 117,0  |
| <b>Douanetarief</b> | 85365080   |
| <b>GTIN</b>         | 8052878069124  |

## Technische gegevens

|  |  |
|--|--|
| <b>Approvals</b>                         | CE, (UL-CSA 030F1-030FA-030FC-030FAA-030FCR only)  |
| <b>Compliance with standards</b>         | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2   |
| <b>Operating temperatures</b>            | -25° ÷ +65°C                                       |
| <b>Protection degree</b>                 | IP65 (IEC-EN60529)                                 |
| <b>Mechanical durability</b>             | 500.000 Operations                                 |
| <b>External bezel material</b>           | Chromed zinc alloy                                 |
| <b>Button material</b>                   | PA Polyamide                                       |
| <b>Housing material</b>                  | PA Polyamide + chrome                              |
| <b>Fixing diameter</b>                   | 30.5mm - Thickness 1÷6mm                           |
| <b>Tightening torque</b>                 | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)                        |
| <b>Actuation type</b>                    | With mechanical latching - twist to release        |
| <b>Protection against electric shock</b> | Class II (IEC-EN61140)                             |
| <b>Contact block</b>                     | Included   |
| <b>Contact block characteristics</b>     | See technical features of 030FAP - 030FCP - 030F1P |
| <b>Warranty period</b>                   | 18 months  |

# Technische tekeningen

