

Fiche technique

030PFFBAFC

Bouton-poussoir coup de poing Ø 60, rouge, déverrouillage par clé K37, 1 N.C.



Caractéristiques

Portée	Boutons-poussoirs d'arrêt d'urgence Ø 30
Composant	Coup de poing Ø 60, déverrouillage par clé
Code	030PFFBAFC
Désignation des marchandises	Bouton-poussoir coup de poing Ø 60, rouge, déverrouillage par clé K37, 1 N.C.
Couleur	Rosso
Poids	179,0
Tarif douanier	85365080
GTIN	8052878030179

Données techniques

Approvals	CE, (UL-CSA 030F1-030FA-030FC-030FAA-030FCR only)
Compliance with standards	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
Operating temperatures	-25° ÷ +65°C
Protection degree	IP65 (IEC-EN60529)
Mechanical durability	500.000 Operations
External bezel material	Chromed zinc alloy
Button material	PA Polyamide
Housing material	PA Polyammide + chrome
Fixing diameter	30.5mm - Thickness 1÷6mm
Tightening torque	2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)
Actuation type	With mechanical latching - twist to release
Protection against electric shock	Class II (IEC-EN61140)
Contact block	Included
Contact block characteristics	See technical features of 030FAP - 030FCP - 030F1P
Warranty period	18 months

Dessins techniques

