

## Scheda Dati

030PFGEB

Botão com proteção estendida, fio painel, temporário, branco



## Caratteristiche

|                         |  |
|-------------------------|--|
| <b>Gama</b>             | Botões não luminosos Ø 30                                    |
| <b>Componente</b>       | Botões com proteção estendida                                |
| <b>Código</b>           | 030PFGEB   |
| <b>Descrição</b>        | Botão com proteção estendida, fio painel, temporário, branco |
| <b>Peso</b>             | 36,0   |
| <b>Tariffa doganale</b> | 85365080   |
| <b>GTIN</b>             | 8052878030315  |

## Dati tecnici

|  |  |
|--|--|
| <b>Approvals</b>                                   | CE, UL, CSA                                      |
| <b>Compliance with standards</b>                   | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| <b>Compliance with standards</b>                   | UNI CEI EN 45545-2, CEI EN 61373                 |
| <b>Operating temperatures</b>                      | -25° ÷ +65°C                                     |
| <b>Environmental operating values</b>              | +25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30)     |
| <b>Protection degree</b>                           | IP65 (IEC-EN60529)                               |
| <b>Protection against impact</b>                   | IK04 (IEC-EN62262)                               |
| <b>Mechanical durability</b>                       | 3.000.000 Operations                             |
| <b>Shock resistance</b>                            | 30g duration=18ms (EN-IEC 60068-2-27)            |
| <b>Shock resistance</b>                            | 50g duration=11ms (EN-IEC 60068-2-27)            |
| <b>Vibration resistance</b>                        | 5g f= 2...500Hz (EN-IEC 60068-2-6)               |
| <b>Contact blocks configuration</b>                | Max no. 6 blocks (3+3)                           |
| <b>Button/mushroom material (illuminated type)</b> | PC Polycarbonate                                 |
| <b>Button or knob material</b>                     | PA Polyamide                                     |
| <b>External bezel material</b>                     | Anodized aluminum                                |
| <b>Locking ring material</b>                       | Zamak zinc alloy                                 |
| <b>Fixing diameter</b>                             | 30.5mm - Thickness 1÷6mm                         |
| <b>Tightening torque</b>                           | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)                      |
| <b>Actuation type</b>                              | Spring return                                    |
| <b>Protection against electric shock</b>           | Class I (IEC-EN61140)                            |
| <b>Warranty period</b>                             | 18 months  |

## Disegni tecnici

