Hoja de datos

030PFGEV
Pulsador con guarda extendida, hilo panel, momentáneo, verde

Características

Rango	Pulsadores no luminosos Ø 30
Componente	Pulsadores con guarda extendida
Código	030PFGEV
Descripción	Pulsador con guarda extendida, hilo panel, momentáneo, verde
Color	Verde
Peso	36,0
Arancel aduanero	85365080
GTIN	8052878030384

Datos técnicos

Approvals	CE, UL, CSA
Compliance with standards	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
Compliance with standards	UNI CEI EN 45545-2, CEI EN 61373
Operating temperatures	-25° ÷ +65°C
Environmental operating values	+25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30)
Protection degree	IP65 (IEC-EN60529)
Protection against impact	IK04 (IEC-EN62262)
Mechanical durability	3.000.000 Operations
Shock resistance	30g duration=18ms (EN-IEC 60068-2-27)
Shock resistance	50g duration=11ms (EN-IEC 60068-2-27)
Vibration resistance	5g f= 2...500Hz (EN-IEC 60068-2-6)
Contact blocks configuration	Max no. 6 blocks (3+3)
Button/mushroom material (illuminated type)	PC Polycarbonate
Button or knob material	PA Polyamide
External bezel material	Anodized aluminum
Locking ring material	Zamak zinc alloy
Fixing diameter	30.5mm - Thickness 1÷6mm
Tightening torque	2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)
Actuation type	Spring return
Protection against electric shock	Class I (IEC-EN61140)

Warranty period	18 months

Dibujos técnicos