

## Scheda Dati

030PFPPA

Protección pulsador hilo panel, precintable, aluminio



## Caratteristiche

<b>Rango</b>	Accesorios Ø 30
<b>Componente</b>	Protecciones precintables para pulsadores
<b>Código</b>	030PFPPA
<b>Descripción</b>	Protección pulsador hilo panel, precintable, aluminio
<b>Peso</b>	20,0
<b>Tariffa doganale</b>	85365080
<b>GTIN</b>	8052878031176

## Dati tecnici

<b>Approvals</b>	CE
<b>Operating temperatures</b>	-40° ÷ +80°C
<b>Protection degree</b>	IP20 (IEC-EN60529)
<b>Protection against impact</b>	IK07 (IEC-EN62262)
<b>Material</b>	Aluminium alloy
<b>External treatment</b>	Natural or black anodizing
<b>Gasket material</b>	Transparent silicon rubber
<b>Spring material</b>	Stainless steel AISI 302
<b>Sealing</b>	Lockable by lead sealing wire - D.2mm max
<b>Use</b>	Suitable for 032 flush panel operators only
<b>Thickness</b>	1mm - use it on panels of 5mm thickness max
<b>Spring loaded opening lid</b>	Spring holds the lid in closed position
<b>Warranty period</b>	18 months

## Disegni tecnici

