

## Fiche technique

030PFPS2P-0D

Clapet de protection scellable pour activation bouton tournant à droite, montage affleurant, noir



## Caractéristiques

<b>Portée</b>	Accessoires Ø 30
<b>Composant</b>	Protections scellables pour boutons tournants
<b>Code</b>	030PFPS2P-0D
<b>Désignation des marchandises</b>	Clapet de protection scellable pour activation bouton tournant à droite, montage affleurant, noir
<b>Couleur</b>	Nero
<b>Poids</b>	16,0
<b>Tarif douanier</b>	85365080
<b>GTIN</b>	8052878031183

## Données techniques

<b>Approvals</b>	CE
<b>Operating temperatures</b>	-40° ÷ +80°C
<b>Protection degree</b>	IP20 (IEC-EN60529)
<b>Protection against impact</b>	IK07 (IEC-EN62262)
<b>Material</b>	Aluminium alloy
<b>External treatment</b>	Natural or black anodizing
<b>Gasket material</b>	Transparent silicon rubber
<b>Spring material</b>	Stainless steel AISI 302
<b>Sealing</b>	Lockable by lead sealing wire - D.2mm max
<b>Use</b>	Suitable for 032 flush panel operators only
<b>Thickness</b>	1mm - use it on panels of 5mm thickness max
<b>Spring loaded opening lid</b>	Spring holds the lid in closed position
<b>Warranty period</b>	18 months

## Dessins techniques

