

Fiche technique

030PFPSBA

Clapet de protection scellable avec verrouillage, montage affleurant, pour bouton tournant, aluminium



Caractéristiques

| | |
|-------------------------------------|---|
| Portée | Accessoires Ø 30 |
| Composant | Protections scellables boutons tournants avec verrouillage |
| Code | 030PFPSBA |
| Désignation des marchandises | Clapet de protection scellable avec verrouillage, montage affleurant, pour bouton tournant, aluminium |
| Poids | 25,0 |
| Tarif douanier | 85365080 |
| GTIN | 8052878031213 |

Données techniques

| | |
|----------------------------------|---|
| Approvals | CE |
| Operating temperatures | -40° ÷ +80°C |
| Protection degree | IP20 (IEC-EN60529) |
| Protection against impact | IK07 (IEC-EN62262) |
| Material | Aluminium alloy |
| External treatment | Natural or black anodizing |
| Gasket material | Transparent silicon rubber |
| Spring material | Stainless steel AISI 302 |
| Sealing | Lockable by lead sealing wire - D.2mm max |
| Use | Suitable for 032 flush panel operators only |
| Thickness | 1mm - use it on panels of 5mm thickness max |
| Spring loaded opening lid | Spring holds the lid in closed position |
| Warranty period | 18 months |

Dessins techniques

