

## Hoja de datos

030PFUSBC

Toma USB 3.0 tipo C-A (hembra-hembra), hilo panel



## Características

<b>Rango</b>	Tomas USB
<b>Componente</b>	Toma USB 3.0 hembra-hembra
<b>Código</b>	030PFUSBC
<b>Descripción</b>	Toma USB 3.0 tipo C-A (hembra-hembra), hilo panel
<b>Color</b>	Nero
<b>Peso</b>	39,0
<b>Arancel aduanero</b>	85366990
<b>GTIN</b>	8052878068936

## Datos técnicos

<b>Approvals</b>	CE
<b>Compliance with standards</b>	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
<b>Compliance with standards</b>	UNI CEI EN 45545-2
<b>Compliance with standards</b>	USB 3.0 type A
<b>Operating temperatures</b>	-40° ÷ +70°C
<b>Environmental operating values</b>	all climates +40°C and 92% RH
<b>Shock resistance</b>	30g duration=18ms (EN-IEC 60068-2-27)
<b>Vibration resistance</b>	5g f= 2...500Hz (EN-IEC 60068-2-6)
<b>Material</b>	PA Polyamide
<b>External bezel material</b>	Anodized aluminum
<b>Locking ring material</b>	Zamak zinc alloy
<b>Fixing diameter</b>	30.5mm - Thickness 1÷6mm
<b>Tightening torque</b>	1 ÷ 2,5Nm (8.8÷22.1 Lb-in)
<b>USB model</b>	USB 3.0 9 pin, type A-A (female-female)
<b>USB model</b>	USB 3.0 24 pin, type C-A (female-female)
<b>Protection degree</b>	IP20 / IP65 with cap closed (IEC-EN60529)
<b>Insulation resistance</b>	>100MOhm
<b>Contact resistance</b>	<30mOhm
<b>Power on</b>	LED presence checking the right connection
<b>LED durability</b>	>50.000 h
<b>Mechanical lifespan</b>	>15000 insertion cycles

---

**Warranty period**

18 months

---

## Dibujos técnicos

