

Fiche technique

030PFUSBC

Prise USB 3.0 mod. C-A (femelle-femelle), montage affleurant



Caractéristiques

| | |
|-------------------------------------|--|
| Portée | Prises USB |
| Composant | Prise USB 3.0 femelle-femelle |
| Code | 030PFUSBC |
| Désignation des marchandises | Prise USB 3.0 mod. C-A (femelle-femelle), montage affleurant |
| Couleur | Nero |
| Poids | 39,0 |
| Tarif douanier | 85366990 |
| GTIN | 8052878068936 |

Données techniques

| | |
|---------------------------------------|--|
| Approvals | CE |
| Compliance with standards | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| Compliance with standards | UNI CEI EN 45545-2 |
| Compliance with standards | USB 3.0 type A |
| Operating temperatures | -40° ÷ +70°C |
| Environmental operating values | all climates +40°C and 92% RH |
| Shock resistance | 30g duration=18ms (EN-IEC 60068-2-27) |
| Vibration resistance | 5g f= 2...500Hz (EN-IEC 60068-2-6) |
| Material | PA Polyamide |
| External bezel material | Anodized aluminum |
| Locking ring material | Zamak zinc alloy |
| Fixing diameter | 30.5mm - Thickness 1÷6mm |
| Tightening torque | 1 ÷ 2,5Nm (8.8÷22.1 Lb-in) |
| USB model | USB 3.0 9 pin, type A-A (female-female) |
| USB model | USB 3.0 24 pin, type C-A (female-female) |
| Protection degree | IP20 / IP65 with cap closed (IEC-EN60529) |
| Insulation resistance | >100MΩ |
| Contact resistance | <30mΩ |
| Power on | LED presence checking the right connection |
| LED durability | >50.000 h |

| | |
|----------------------------|-------------------------|
| Mechanical lifespan | >15000 insertion cycles |
| Warranty period | 18 months |

Dessins techniques

