

## Scheda Dati

030PFUSBC  
Tomada USB 3.0 tipo C-A (fêmea-fêmea), fio painel



## Caratteristiche

|                  |                                                   |
|------------------|---------------------------------------------------|
| Gama             | Tomadas USB                                       |
| Componente       | Tomada USB 3.0 fêmea-fêmea                        |
| Código           | 030PFUSBC                                         |
| Descrição        | Tomada USB 3.0 tipo C-A (fêmea-fêmea), fio painel |
| Cor              | Nero                                              |
| Peso             | 39,0                                              |
| Tariffa doganale | 85366990                                          |
| GTIN             | 8052878068936                                     |

## Dati tecnici

|                                |                                                  |
|--------------------------------|--------------------------------------------------|
| Approvals                      | CE                                               |
| Compliance with standards      | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| Compliance with standards      | UNI CEI EN 45545-2                               |
| Compliance with standards      | USB 3.0 type A                                   |
| Operating temperatures         | -40° ÷ +70°C                                     |
| Environmental operating values | all climates +40°C and 92% RH                    |
| Shock resistance               | 30g duration=18ms (EN-IEC 60068-2-27)            |
| Vibration resistance           | 5g f= 2...500Hz (EN-IEC 60068-2-6)               |
| Material                       | PA Polyamide                                     |
| External bezel material        | Anodized aluminum                                |
| Locking ring material          | Zamak zinc alloy                                 |
| Fixing diameter                | 30.5mm - Thickness 1÷6mm                         |
| Tightening torque              | 1 ÷ 2,5Nm (8.8÷22.1 Lb-in)                       |
| USB model                      | USB 3.0 9 pin, type A-A (female-female)          |
| USB model                      | USB 3.0 24 pin, type C-A (female-female)         |
| Protection degree              | IP20 / IP65 with cap closed (IEC-EN60529)        |
| Insulation resistance          | >100MOhm                                         |
| Contact resistance             | <30mOhm                                          |
| Power on                       | LED presence checking the right connection       |
| LED durability                 | >50.000 h                                        |
| Mechanical lifespan            | >15000 insertion cycles                          |

Warranty period

18 months

Disegni tecnici

