

## Hoja de datos

030PIAFA

Pulsador con guarda entera, naranja, N.O.



## Características

|                  |   |
|------------------|---|
| Rango            | Pulsadores no luminosos Ø 30              |
| Componente       | Pulsadores con guarda entera              |
| Código           | 030PIAFA                                  |
| Descripción      | Pulsador con guarda entera, naranja, N.O. |
| Color            | Arancio                                   |
| Peso             | 75,0                                      |
| Arancel aduanero | 85365080                                  |
| GTIN             | 8052878031350                             |

## Datos técnicos

|   |  |
|---|--|
| Approvals                                   | CE, (UL-CSA 030F1-030FA-030FC-030FAA-030FCR only)  |
| Compliance with standards                   | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2   |
| Operating temperatures                      | -25° ÷ +65°C                                       |
| Protection degree                           | IP65 (IEC-EN60529)                                 |
| Mechanical durability                       | 3.000.000 Operations                               |
| Button/mushroom material (illuminated type) | PC Polycarbonate                                   |
| External bezel material                     | Chromed zinc alloy                                 |
| Housing material                            | PA Polyamide + chrome                              |
| Fixing diameter                             | 30.5mm - Thickness 1÷6mm                           |
| Tightening torque                           | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)                        |
| Actuation type                              | Spring return                                      |
| Protection against electric shock           | Class II (IEC-EN61140)                             |
| Contact block                               | Included   |
| Contact block characteristics               | See technical features of 030FAP - 030FCP - 030F1P |
| Warranty period                             | 18 months  |

# Dibujos técnicos

