
# Hoja de datos

030PIBLFC
Pulsador con guarda entera, azul, N.C.





## Características

| | |
|---|---|
| **Rango** | Pulsadores no luminosos Ø 30 |
| **Componente** | Pulsadores con guarda entera |
| **Código** | 030PIBLFC |
| **Descripción** | Pulsador con guarda entera, azul, N.C. |
| **Color** | Blu |
| **Peso** | 75,0 |
| **Arancel aduanero** | 85365080 |
| **GTIN** | 8052878031411 |

## Datos técnicos

| | |
|---|---|
| **Approvals** | CE, (UL-CSA 030F1-030FA-030FC-030FAA-030FCR only) |
| **Compliance with standards** | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| **Operating temperatures** | -25° ÷ +65°C |
| **Protection degree** | IP65 (IEC-EN60529) |
| **Mechanical durability** | 3.000.000 Operations |
| **Button/mushroom material (illuminated type)** | PC Polycarbonate |
| **External bezel material** | Chromed zinc alloy |
| **Housing material** | PA Polyammide + chrome |
| **Fixing diameter** | 30.5mm - Thickness 1÷6mm |
| **Tightening torque** | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in) |
| **Actuation type** | Spring return |
| **Protection against electric shock** | Class II (IEC-EN61140) |
| **Contact block** | Included |
| **Contact block characteristics** | See technical features of 030FAP - 030FCP - 030F1P |
| **Warranty period** | 18 months |

## Dibujos técnicos

