


## Scheda Dati

030PIBLFC

Painike kokonaisella suojuksella, sininen, N.C.



## Caratteristiche

|                  |                                                 |
|------------------|-------------------------------------------------|
| Range            | Normaalit painikkeet Ø 30                       |
| Componente       | Painikkeet kokonaisella suojuksella             |
| Code             | 030PIBLFC                                       |
| Kuvaus           | Painike kokonaisella suojuksella, sininen, N.C. |
| Väriä            | Blu                                             |
| Peso             | 75,0                                            |
| Tariffa doganale | 85365080                                        |
| GT               | 8052878031411                                   |

## Dati tecnici

|                                             |                                                    |
|---------------------------------------------|----------------------------------------------------|
| Approvals                                   | CE, (UL-CSA 030F1-030FA-030FC-030FAA-030FCR only)  |
| Compliance with standards                   | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2   |
| Operating temperatures                      | -25° ÷ +65°C                                       |
| Protection degree                           | IP65 (IEC-EN60529)                                 |
| Mechanical durability                       | 3.000.000 Operations                               |
| Button/mushroom material (illuminated type) | PC Polycarbonate                                   |
| External bezel material                     | Chromed zinc alloy                                 |
| Housing material                            | PA Polyamide + chrome                              |
| Fixing diameter                             | 30.5mm - Thickness 1÷6mm                           |
| Tightening torque                           | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)                        |
| Actuation type                              | Spring return                                      |
| Protection against electric shock           | Class II (IEC-EN61140)                             |
| Contact block                               | Included                                           |
| Contact block characteristics               | See technical features of 030FAP - 030FCP - 030F1P |
| Warranty period                             | 18 months                                          |

Disegni tecnici

