

## Datenblatt

030PIRF1

Drucktaster mit Vollschutz, rot, N.O.+N.C.



## Merkmale

|                        |  |
|------------------------|--|
| <b>Baureihe</b>        | Unbeleuchtete Taster Ø 30                  |
| <b>Komponenten</b>     | Drucktaster mit Vollschutz                 |
| <b>Artikel-Nr.</b>     | 030PIRF1                                   |
| <b>Beschreibung</b>    | Drucktaster mit Vollschutz, rot, N.O.+N.C. |
| <b>Farbe</b>           | Rosso                                      |
| <b>Gewicht - gr</b>    | 100,0                                      |
| <b>Zolltarifnummer</b> | 85365080                                   |
| <b>GTIN</b>            | 8052878031596                              |

## Technische Daten

|  |  |
|--|--|
| <b>Approvals</b>                                   | CE, (UL-CSA 030F1-030FA-030FC-030FAA-030FCR only)  |
| <b>Compliance with standards</b>                   | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2   |
| <b>Operating temperatures</b>                      | -25° ÷ +65°C                                       |
| <b>Protection degree</b>                           | IP65 (IEC-EN60529)                                 |
| <b>Mechanical durability</b>                       | 3.000.000 Operations                               |
| <b>Button/mushroom material (illuminated type)</b> | PC Polycarbonate                                   |
| <b>External bezel material</b>                     | Chromed zinc alloy                                 |
| <b>Housing material</b>                            | PA Polyamide + chrome                              |
| <b>Fixing diameter</b>                             | 30.5mm - Thickness 1÷6mm                           |
| <b>Tightening torque</b>                           | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)                        |
| <b>Actuation type</b>                              | Spring return                                      |
| <b>Protection against electric shock</b>           | Class II (IEC-EN61140)                             |
| <b>Contact block</b>                               | Included   |
| <b>Contact block characteristics</b>               | See technical features of 030FAP - 030FCP - 030F1P |
| <b>Warranty period</b>                             | 18 months  |

# Technische Zeichnungen

