


## Scheda Dati

030PNGF1

Bouton-poussoir affleurant, demi-collerette, jaune, N.O.+N.C.



## Caratteristiche

|                                     |   |
|-------------------------------------|---|
| <b>Portée</b>                       | Boutons-poussoirs non-lumineux Ø 30                           |
| <b>Componente</b>                   | Affleurants, demi-collerette                                  |
| <b>Code</b>                         | 030PNGF1  |
| <b>Désignation des marchandises</b> | Bouton-poussoir affleurant, demi-collerette, jaune, N.O.+N.C. |
| <b>Couleur</b>                      | Giallo  |
| <b>Peso</b>                         | 93,0  |
| <b>Tariffa doganale</b>             | 85365080  |
| <b>GTIN</b>                         | 8052878031862   |

## Dati tecnici

|  |  |
|--|--|
| <b>Approvals</b>                                   | CE, (UL-CSA 030F1-030FA-030FC-030FAA-030FCR only)  |
| <b>Compliance with standards</b>                   | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2   |
| <b>Operating temperatures</b>                      | -25° ÷ +65°C                                       |
| <b>Protection degree</b>                           | IP65 (IEC-EN60529)                                 |
| <b>Mechanical durability</b>                       | 3.000.000 Operations                               |
| <b>Button/mushroom material (illuminated type)</b> | PC Polycarbonate                                   |
| <b>External bezel material</b>                     | Chromed zinc alloy                                 |
| <b>Housing material</b>                            | PA Polyamide + chrome                              |
| <b>Fixing diameter</b>                             | 30.5mm - Thickness 1÷6mm                           |
| <b>Tightening torque</b>                           | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)                        |
| <b>Actuation type</b>                              | Spring return                                      |
| <b>Protection against electric shock</b>           | Class II (IEC-EN61140)                             |
| <b>Contact block</b>                               | Included   |
| <b>Contact block characteristics</b>               | See technical features of 030FAP - 030FCP - 030F1P |
| <b>Warranty period</b>                             | 18 months  |

# Disegni tecnici

