

Scheda Dati

030PPFIBL

Pulsador hilo panel, estable, azul



Caratteristiche

Rango	Pulsadores no luminosos Ø 30
Componente	Pulsadores con guarda
Código	030PPFIBL
Descripción	Pulsador hilo panel, estable, azul
Color	Blu
Peso	35,0
Tariffa doganale	85365080
GTIN	8052878032067

Dati tecnici

Approvals	CE, UL, CSA
Compliance with standards	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
Compliance with standards	UNI CEI EN 45545-2, CEI EN 61373
Operating temperatures	-25° ÷ +65°C
Environmental operating values	+25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30)
Protection degree	IP65 (IEC-EN60529)
Protection against impact	IK04 (IEC-EN62262)
Mechanical durability	500.000 Operations
Shock resistance	30g duration=18ms (EN-IEC 60068-2-27)
Shock resistance	50g duration=11ms (EN-IEC 60068-2-27)
Vibration resistance	5g f= 2...500Hz (EN-IEC 60068-2-6)
Contact blocks configuration	Max no. 4 blocks (2+2)
Button or knob material	PA Polyamide
External bezel material	Anodized aluminum
Locking ring material	Zamak zinc alloy
Fixing diameter	30.5mm - Thickness 1÷6mm
Tightening torque	2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)
Actuation type	Push-Push (maintained position)
Protection against electric shock	Class I (IEC-EN61140)
Warranty period	18 months

Disegni tecnici

